

REQUEST FOR QUOTATION

Date: 12 March 2024 RFQ No.: **100-24-01-068**

Name of Company:	
Address:	
Name of Store/Shop:	
Address:	
TIN:	
PhilGEPS Registration Number:	

The **City Government of Pasig**, through the Bids and Awards Committee (BAC), intends to procure **Supply and Delivery of Various ICT Equipment – City Health Office** with an Approved Budget for the Contract (ABC) of **Php 734,396.16**, in accordance with **Section 53.9** of the 2016 revised Implementing Rules and Regulations of Republic Act No. 9184. Please quote your best offer for the item in the table below.

The Project shall be awarded as One Project having several items grouped into several lots, which shall be awarded as separate contracts per lot. Quotations received exceeding each total Cost per Item and/or the total Approved Budget for the Contract shall be rejected.

					Approved Budget		Price Offer	
ltem No.	Item Description	Brand Name* (PLEASE DO NOT LEAVE BLANK)	QTY	UOM	Unit Cost	Total Cost	Unit cost	Total Cost
	LOT 1							
1	Printer, -Digital color copier which is capable of color scanning, printing and fax with automatic document feeder -Printing technology; Inkjet or equivalent -Printing speed of at least up to 33.0ppm/ 15ppm -Paper capacity of at least 30 sheets (A4 paper), 10 sheets (Legal) -Printer resolution of at least 5760 x 1440 dpi -Capable of printing to various paper sizes, up to A4 -Capable of borderless printing up to 4R -Uses Dye Inks (Black, Magenta, Cyan and Yellow) -Supports USB, LAN, Wifi and Wifi direct and other network management protocol -Must be supported with applications/utilities from the manufacturer to optimized device functionalities		11	unit	16,312.68	179,439.48		



		1			1	1	1	
	-Must be supported by the latest version of							
	Windows OS and Mac OS							
	-With at least 1 year warranty on parts and							
	services							
2	Ink (Black), -Compatible with Procured		104	bottles	350.00	36,400.00		
	Printer							
3	Ink (Cyan), -Compatible with Procured		51	bottles	350.00	17,850.00		
	Printer							
4	Ink (Yellow), -Compatible with Procured		51	bottles	350.00	17,850.00		
	Printer							
5	Ink (Magenta), -Compatible with Procured		51	bottles	350.00	17,850.00		
	Printer							
		Sub	Total:		269,	389.48		
	LOT 2							
6	Laptop, -Processor: At least 10 cores, 12		4	unit	86,201.67	344,806.68		
	threads, 12MB cache, at least 4.6 GHz							
	Maximum turbo frequency							
	-Memory: At least 8GB RAM							
	-Storage: at least 256GB SSD M.2 for OS, at							
	least 1TB HDD for file storage							
	-OS: Pre-installed Windows 11 Pro 64Bit							
	-Webcam: Integrated HD 720p							
	-Display: at least 15-inch FHD 1920 x 1080							
	resolution							
	-LAN: Gigabit 10/100/1000							
	-Bluetooth: Latest Bluetooth Technology							
	-Battery: Li-on Battery life at least 8 hours							
	-Adaptor: AC Adapter Port: Type-C							
	-With Numeric Keypads							
	-With Energy Star 8.0 Rating,							
	-With Top Load Carrying Case or Backpack,							
	Orginally issued by the manufacturer.							
	-3 years warranty on parts and services, 1-							
	year warranty on battery.							
	-Bundle with MS Office Home and Business							
	2021 with Electronic Software Distribution							
	(ESD)- is the secure delivery of a product key							
	directly to consumers and small business.							
	Customer can instantly download/ activate							
	software after purchase. Product is live and							
	usable when delivered. 1 install only,							
	Commercial Use. Perpetual							
	-Applications: Word, Excel, PowerPoint, One							
	Note, Outlook. can be installed either							
	Windows 10 & 11 or Mac devices.							
7	Desktop, -Processor: At least 6 cores, 12		1	set	85,200.00	85,200.00		
	threads, Maximum Turbo Frequency of at							
	least 4.4GHz, at least 18MB Cache							
	-Monitor: LED Technology at least 23 inches,							
	with VGA, HDMI, Display Ports, at least FHD							
	(1920 x 1080)							
	-Storages: at least 256 GB SSD M.2 for OS							
	and at least 1 TB HDD for file storage							
	-Memory: at least 8GB							
	-With USB Wired Keyboard and Mouse							
	-Must be LAN Ready (Gigabit 10/100/1000)							
	-With pre-installed Windows 11 Pro							

Caruncho Avenue, Brgy. San Nicolas, Pasig City, Philippines 1600

(02) 8643-1111 * (02) 8641-1111 loc 1461 * bidsandawards@pasigcity.gov.ph *

Page 2 of 6 | RFQ No. 100-24-01-068 | RLD

-At least 3 years warranty on parts and services With bundle uninterrupted power supply Technical Specifications: -At least 360 Watts/650VA - Output Frequency: -50/60 Hz +/- 1 Hz Sync to mains - Topology- Line interactive or any topology that would protect the end user against the following: power railure, power sag, power surge, under voltage and over-voltage. - Waveform type: within the ranges of stepped approximation sinewave to a pure sinewave - Transfer time: at most 10ms - Input Frequency- 50/60 Hz +/- 3 Hz Autosensing - Input Protection - circuit breaker or equivalent - Haat at least 4 uotitus - Type of input protection - circuit breaker or equivalent - Battery type-Lead-acid battery - Recharge time: 6 hours or more Autosensing - More to Cody - 1 sets 12V - Battery type-Lead-acid battery - Recharge time: 6 hours or more equivalent - Battery type-Lead-acid battery - Recharge time: 6 hours or more - Mornial Battery Voltage at least 12V - Battery type-Lead-acid battery - Recharge time: 6 hours or more - Mornial Battery Voltage at least 12V - Battery type - Lead-acid battery - Recharge time: 6 hours or more - Must have audible alarm when overloaded - Surge energy time; 15 houlsor higher - Must have audible alarm when overloaded - Surge energy time; 16 hourso rhome to trade and Industry's Bureau of Philippine Standards (DTI-BPS) - With standard warranty- 2 years repair or replacement - Bundle with MS Office Home and business 2021 with electronic Software Distribution (ESD) - is the seure delivery of a product key directly to consumers and small business. 2021 with electronic Software Distribution (ESD) - is the enstable deliver Window - Applications: Word, Power Point, One Note, Outhok. Can be instable (deliver Mindow - Applications: Word, Power Point, One Note, Outhok. Can be instable (deliver Window - Applications: Word, Power Point, One Note, Outhok. Can be instable (deliver Window - Applications: Word, Power Point, One Note, Outhok. Can be instable (deliver Window - Applications: Word, Power Point, One No	LOT 3	501		+30,000		
services With bundle uninterrupted power supply Technical Specifications: - At least 360 Watts/650VA - Output Frequency: -50/50 Hz +/- 1 Hz Sync to mains - Topology- Line interactive or any topology that would protect the end user against the following: power failure, power sag, power surge, under voltage and over-voltage. - Waveform type- within the ranges of stepped approximation sinewave to a pure sinewave - Transfer time: at most 10ms - Input Frequency: -50/60 Hz +/- 3 Hz Autosensing - Input Frequency: -50/60 Hz +/- 3 Hz Autosensing - Input rototage range for main operations: 140V to 300V or higher - Number of Power Cords-1 - Has at least 4 uotputs - Type of input protection- circuit breaker or equivalent - Battery type- Lead-acid battery - Recharge time: 6 hours or more - Nominal Battery Voltage at least 12V - Battery: at least 24 Volt-Amp-Hour Capacity - Control Panel: LED Statu Silpaly with online: on battery - Must have acidible alarm when on battery, distinctive alarm when ouvelraded - Surge energy rating: 156 Joules on higher - Must have acidible alarm when ouvelraded - Surge energy rating: 156 Joules on higher - Must have acidible alarm when outer - Must have acidible alarm when outer - Surge energy rating: 156 Joules on higher - Must conform with ENVIEC 60240-1, ENVIEC 60204-2, or ther i Coal or international standards on safety of machinery duly recognized by the Department of Trade and Industry's Bureau of Philippine Standards (DTI-BPE) - With standard warranty- 2 years repair or replacement - Bundle with MS Office Home and business 2021 with electronic Software Distribution (SD) - site Secure delivery of a product key directly to consumers and small business. 2021 with electronic Software Distribution (SD) - site secure delivery of a product key directly to consumers and small business. 2021 with electronic Software Distribution (SD) - site secure delivery of a product key directly to consumers and small business. 2021 with electronic Softwa		Sul	SubTotal: 430,006.68		.68	
services With bundle uninterrupted power supply Technical Specifications: - At least 360 wats/650VA - Output Frequency: -50/60 Hz +/- 1 Hz Sync to mains - Topology- Line interactive or any topology that would protect the end user againts the following: power failure, power sag, power surge, under voltage and over-voltage. - Waveform type- within the ranges of stepped approximation sinewave to a pure sinewave - Transfer time: at most 10ms - Input Frequency50/50 Hz +/- 3 Hz Autosensing - Input voltage range for main operations: 1 Aput solage range range for main operations: 1 Aput						
services With bundle uninterrupted power supply Technical Specifications: At least 360 Watty/650VA Output Frequency: -50/60 Hz +/- 1 Hz Sync to mains Topology- Line interactive or any topology that would protect the end user against the following: power failure, power sag, power surge, under voltage and over-voltage. Waveform type- within the ranges of stepped approximation sinewave to a pure sinewave Transfer time: at most 10ms -input Frequency: -50/50 Hz +/- 3 Hz Autosensing -input Voltage range for main operations: 140V to 300V or higher -Number of Power Cords-1 -Has at least 4 output5 -Type of input protection- circuit breaker or equivalent Battery type-Lead-acid battery -Recharge time: 6 hours or more -Nominal Battery Voltage at least 12V -Battery: type-Lead-acid battery -Must hord much how battery, and continue: one battery -Must have audible alarm when on battery, distinctive alarm when owerloaded -Surge energy rating: 156 Joules or higher -Must confor which WE N/EC 60204-1, EN/IEC 60204-2, or other local or international standards on safety of machinery duly recognized by the Department of Trade and Industry's Bureau of Philippine Standards (DTI-BPS) -With standard warranty- 2 years repair or replacement -Bundle with MS Office Home and business 2021 with electronic Software Distribution (ESD) - is the secure delivery of a product key directly to consumers and small business. 2021 with electronic Software Distribution (ESD) - is the secure delivery of a product key directly to consumers and small business. 2021 with electronic Software Distribution (ESD) - is the secure delivery of a product key directly to consumers and small business. 2021 with electronic Software Distribution (ESD) - is the secure delivery of a product key directly to consumers and small business. 2021 with electronic Software Distribution (ESD) - is the secure delivery of a product key directly to consumers and small business. 2021 with electronic Software Distribution (ESD) - i						
services With bundle uninterrupted power supply Technical Specifications: - At least 360 Watts/S50VA -Output Frequency: -50/60 Hz +/- 1 Hz Sync to mains -Topology. Line interactive or any topology that would protect the end user agains the following: power failure, power sage, power surge, under voltage and over-voltage. -Waveform type- within the ranges of stepped approximation sinewave to a pure sinewave -Transfer time: at most 10ms -Input Frequency-: 50/60 Hz +/- 3 Hz Autosensing -Input voltage range for main operations: 140V to 300V or higher -Number of Power Cords-1 -Has at least 4 outputs -Type of input protection- circuit breaker or equivalent -Battery: to Lead-acid battery -Recharge time: 6 hours or more -Nominal Battery Voltage at least 12V -Battery: at least 84 Volt-Mm-Hour Capacity -Control Panel - LED status display with online: on battery -Must have audible alarm when on battery, distinctive alarm when overloaded -Surge energy rating: 156 Joules or higher -Must conform with EN/IEC 60240-1, EN/IEC 60204-2, or other local or international standards on safety of machinery duly recognized by the Department of Trade and Industry's Bureau of Philippine Standards (DTI-B25) -With standard warranty- 2 years repair or replacement -Bundle with MS Office Home and business 2021 with electronic Software Distribution (ESD) - is the source delivery of a product key directly to consumers and small business. -Customer can instantly download/activate software after purchase, Product Key is live	commercial use. Perpetual					
services With bundle uninterrupted power supply Technical Specifications: - At least 360 Wattx/550VA -Output Frequency: -50/60 Hz +/- 1 Hz Sync to mains - Topology: Line interactive or any topology that would protect the end user agains the following: power failure, power sage, power surge, under voltage and over-voltage. - Waveform type- within the ranges of stepped approximation sinewave to a pure sinewave - Transfer time: at most 10ms - Input Vitage range for main operations: 140V to 300V or higher - Number of Power Cords-1 - Has at least 4 outputs - Type of input protection- circuit breaker or equivalent - Battery type: Lead-acid battery - Recharge time: a Host 12V - Battery: at least 84 Volt-Amp-Hour Capacity - Control Panel: LED status display with online: on battery - Must have audible alarm when on battery, distinctive alarm when overloaded - Surge energy rating: 156 Joules of higher - Must conform with EN/IEC 60240-1, EN/IEC 60204-2, or other local or international standards on safety of machinery duly recognized by the Department of Trade and Industry's Bureu of Philippine Standards (DT-B9) - With standard warranty- 2 years repair or replacement - Bundle with MS Office Home and business - Customer can instantity download/activate						
services With bundle uninterrupted power supply Technical Specifications: - At least 360 Watts/S50VA -Output Frequency: -50/60 Hz +/- 1 Hz Sync to mains - Topology. Line interactive or any topology that would protect the end user agains the following: power failure, power sage, power surge, under voltage and over-voltage. - Waveform type- within the ranges of stepped approximation sinewave to a pure sinewave - Transfer time: at most 10ms - Input voltage range for main operations: 140V to 300V or higher - Number of Power Cords-1 - Has at least 4 outputs - Type of input protection- circuit breaker or equivalent - Battery: to Lead-acid battery - Recharge time: 6 hours or more - Nominal Battery Voltage at least 12V - Battery: at least 4 Volt-Amp-Hour Capacity - Control Panel- LED status display with online: on battery - Must have audible alarm when on battery, distinctive alarm when oneverbaded - Surge energy rating: 156 Joules or higher - Must have audible alarm when on battery, distinctive alarm when on battery, distinctive alarm when or weredaded - Surge energy rating: 156 Joules or higher - Must have audible alarm when on battery, distinctive alarm when or battery - Must have audible alarm when or battery - Must have audible alarm when or battery - With standard warranty- 2 years repair or replacement - Bundle with MS Office Home and business 2021 with electronic Software Distribution (ESD) - is the secure delivery of a product key directly to consumers and small business.	-					
services With bundle uninterrupted power supply Technical Specifications: -At least 360 Watts/650VA -Output Frequency: -50/60 Hz +/- 1 Hz Sync to mains -Topology- Line interactive or any topology that would protect the end user againts the following: power failure, power sag, power surge, under voltage and over-voltage. -Waveform type- within the ranges of stepped approximation sinewave to a pure sinewave -Transfer time: at most 10ms -Input Frequency- 50/60 Hz +/- 3 Hz Autosensing -Input voltage for main operations: 140V to 300V or higher -Number of Power Cords-1 -Has at least 4 outputs -Type of input protection- circuit breaker or equivalent -Battery type- Lead-acid battery -Recharge time: 6 hours or more -Nominal Battery Voltage at least 12V -Battery: at least 44 Volt-Amp-Hour Capacity -Control Panel- LED status display with online: on battery, -Must have audible alarm when on battery, distinctive alarm when ow battery, and continous tome alarm when ow to ateded -Surge energy rating: 156 Joules or higher -Must have audible alarm when ob tattery, and continous tom alarm when ow totaded -Surge energy rating: 156 Joules or higher -Must conform with EN/IEC 60240-1, EN/IEC 60204-2, or other local or international standards on safety of machinery duly recognized by the Department of Trade and Industry's Bureau of Philippine Standards (DTI-BPS) -With standard warranty-2 years repair or replacement -Bundle with MS Office Home and business 2021 with electronic Software Distribution	-					
services With bundle uninterrupted power supply Technical Specifications: -At least 360 Watts/650VA -Output Frequency: -50/60 Hz +/- 1 Hz Sync to mains -Topology- Line interactive or any topology that would protect the end user againts the following: power failure, power sag, power surge, under voltage and over-voltage. -Waveform type- within the ranges of stepped approximation sinewave to a pure sinewave -Transfer time: at most 10ms -Input Frequency- 50/60 Hz +/- 3 Hz Autosensing -Input orltage range for main operations: 140V to 300V or higher -Number of Power Cords-1 -Has at least 4 outputs -Type of input protection- circuit breaker or equivalent -Battery type- Lead-acid battery -Recharge time: 6 hours or more -Nominal Battery Volatge at least 12V -Battery volateg at l						
services With bundle uninterrupted power supply Technical Specifications: -At least 360 Watts/650VA -Output Frequency: -50/60 Hz +/- 1 Hz Sync to mains -Topology- Line interactive or any topology that would protect the end user againts the following: power failure, power sag, power surge, under voltage and over-voltage. -Waveform type- within the ranges of stepped approximation sinewave to a pure sinewave -Transfer time: at most 10ms -Input Frequency- 50/60 Hz +/- 3 Hz Autosensing -Input troutour or for order - 1 - 3 Hz Autosensing -Input protection- circuit breaker or equivalent -Recharge time: 6 hours or more -Nominal Battery Voltage at least 12V -Battery: at least 4 0 utputs -Type of input protection- circuit breaker or equivalent -Battery type- Lead-acid battery -Recharge time: 6 hours or more -Nominal Battery Voltage at least 12V -Battery: at least 4 Volt-May-Hour Capacity -Control Panel- LED status display with online: on battery -Must have audible alarm when on battery, distinctive alarm when ow battery, and continous tone alarm when ownorded -Surge energy rating: 155 Joules or higher -Must have audible alarm when ownorded -Surge energy rating: 155 Joules or higher -Must have audible alarm when ownorded -Surge energy rating: 155 Joules or higher -Must conform with EN/IEC 60240-1, EN/IEC 60204-2, or other local or international standards on safety of machinery duly recognized by the Department of Trade and Industry's Bureau of Philippine Standards (DTI-BPS) -With standard warranty- 2 years repair or replacement						
services With bundle uninterrupted power supply Technical Specifications: -At least 360 Watts/650VA -Output Frequency: -50/60 Hz +/- 1 Hz Sync to mains -Topology- Line interactive or any topology that would protect the end user against the following: power failure, power sag, power surge, under voltage and over-voltage. -Waveform type- within the ranges of stepped approximation sinewave to a pure sinewave -Transfer time: at most 10ms -Input Frequency: 50/60 Hz +/- 3 Hz Autosensing -Input voltage range for main operations: 140V to 300V or higher -Number of Power Cords-1 Has at least 4 outputs -Type of input protection- circuit breaker or equivalent -Battery type-Lead-acid battery -Recharge time: 6 hours or more -Nominal Battery Voltage at least 12V -Battery: at least 84 Volt-Amp-Hour Capacity -Control Panel -LED status display with online: on battery -Must charden when overloaded -Surge energy rating: 156 Joules on higher -Sunder Colar or international standards on safety of machinery duly recognized by the Department of Trade and Industry's Bureau of Philippine Standards (DTI-BPS) -With standard warranty- 2 years repair or						
services With bundle uninterrupted power supply Technical Specifications: -At least 360 Watts/650VA -Output Frequency: -50/60 Hz +/- 1 Hz Sync to mains -Topology- Line interactive or any topology that would protect the end user agains the following: power failure, power sag, power surge, under voltage and over-voltage. -Waveform type- within the ranges of stepped approximation sinewave to a pure sinewave -Transfer time: at most 10ms -Input Frequency: 50/60 Hz +/- 3 Hz Autosensing -Input Voltage range for main operations: 140V to 300V or higher -Number of Power Cords-1 -Has at least 4 outputs -Type of input protection- circuit breaker or equivalent -Battery type- Lead-acid battery -Recharge time: 6 hours or more -Nominal Battery Voltage ta least 12V -Battery: at least 84 Volt-Amp-Hour Capacity -Control Panel- LED status display with online: on battery -Must have audible alarm when no battery, distinctive alarm when low battery, and continues tone alarm when low battery, and continues cone alarm when low battery, and continues cone alarm when low battery, and continues tone alarm when overloaded -Surge energy rating: 156 Joules or higher -Must conform with EN/IEC 60240-1, EN/IEC 60240-2, or other local or international standards on safety of machinery duly recognized by the Department of Trade and idudstry's Bureau of Philippine Standards						
services With bundle uninterrupted power supply Technical Specifications: -At least 360 Watts/650VA Output Frequency: -50/60 Hz +/- 1 Hz Sync to mains -Topology- Line interactive or any topology that would protect the end user agains the following: power failure, power sag, power surge, under voltage and over-voltage. -Waveform type- within the ranges of stepped approximation sinewave to a pure sinewave -Transfer time: at most 10ms -Input Frequency- 50/60 Hz +/- 3 Hz Autosensing -Input of ger ange for main operations: 140V to 300V or higher -Number of Power Cords-1 +Has at least 4 outputs -Type of input protection- circuit breaker or equivalent -Battery type-Lead-acid battery -Recharge time: 6 hours or more -Nominal Battery Volatge at least 12V -Battery: at least 84 Volt-Amp-Hour Capacity -Control Panel- LED status display with online: on battery -Must have audible alarm when on battery, distinctive alarm when ow battery, and continous tone alarm when owtated -Surge energy rating: 156 Joules or higher -Must conform with EN/IEC 60240-1, EN/IEC 60204-2, or other local or international standards on safety of machinery duly recognized by the Department of Trade and	(DTI-BPS)					
services With bundle uninterrupted power supply Technical Specifications: -At least 360 Watts/550VA -Output Frequency: -50/60 Hz +/- 1 Hz Sync to mains -Topology- Line interactive or any topology that would protect the end user againts the following: power failure, power sag, power surge, under voltage and over-voltage. -Waveform type- within the ranges of stepped approximation sinewave to a pure sinewave -Transfer time: at most 10ms -Input Frequency- 50/60 Hz +/- 3 Hz Autosensing -Input totage for main operations: 140V to 300V or higher -Number of Power Cords-1 -Has at least 4 outputs -Type of input protection- circuit breaker or equivalent -Battery type-Lead-acid battery -Recharge time: 6 hours or more -Nominal Battery Volatge at least 12V -Battery: at least 84 Volt-Amp-Hour Capacity -Control Panel- LED status display with online: on battery -Must have audible alarm when on battery, distinctive alarm when owe battery, and continous tom alarm when owe higher -Must conform with EN/IEC 60240-1, EN/IEC 60204-2, or other local or international standards on safety of machinery duly	e , ,					
services With bundle uninterrupted power supply Technical Specifications: -At least 360 Watts/650VA Output Frequency: -50/60 Hz +/- 1 Hz Sync to mains -Topology- Line interactive or any topology that would protect the end user againts the following: power failure, power sag, power surge, under voltage and over-voltage. -Waveform type- within the ranges of stepped approximation sinewave to a pure sinewave -Transfer time: at most 10ms -Input Frequency- 50/60 Hz +/- 3 Hz Autosensing -Input requency- 50/60 Hz +/- 3 Hz Autosensing -Input protection- circuit breaker or equivalent -Battery type- Lead-acid battery -Recharge time: 6 hours or more -Nominal Battery Volatge at least 12V -Battery: at least 84 Volt-Amp-Hour Capacity -Control Panel -LED status display with online: on battery -Must have audible alarm when on battery, distinctive alarm when low battery, and continuous tone alarm when overloaded -Surge energy rating: 155 Joules or higher -Must conform with EN/IEC 60240-1, EN/IEC 60204-2, or other local or international						
services With bundle uninterrupted power supply Technical Specifications: -At least 360 Watts/650VA -Output Frequency: -50/60 Hz +/- 1 HZ Sync to mains -Topology- Line interactive or any topology that would protect the end user against the following: power failure, power sag, power surge, under voltage and over-voltage. -Waveform type- within the ranges of stepped approximation sinewave to a pure sinewave -Transfer time: at most 10ms -Input Frequency- 50/60 Hz +/- 3 Hz Autosensing -Input voltage range for main operations: 140V to 300V or higher -Number of Power Cords-1 -Has at least 4 outputs -Type of input protection- circuit breaker or equivalent -Battery type-Lead-acid battery -Recharge time: 6 hours or more -Nominal Battery Volatge at least 12V -Battery: at least 84 Volt-Amp-Hour Capacity -Control Panel- LED status display with online: on battery -Must have audible alarm when on battery, distinctive alarm when low battery, and continous tone alarm when on battery, distinctive alarm when overloaded -Surge energy rating: 156 Joules or higher -Must conform with EN/IEC 60240-1, EN/IEC						
services With bundle uninterrupted power supply Technical Specifications: -At least 360 Watts/650VA -Output Frequency: -50/60 Hz +/- 1 Hz Sync to mains -Topology- Line interactive or any topology that would protect the end user againts the following: power failure, power sag, power surge, under voltage and over-voltage. -Waveform type- within the ranges of stepped approximation sinewave to a pure sinewave -Transfer time: at most 10ms -Input Voltage range for main operations: 140V to 300V or higher -Number of Power Cords-1 -Has at least 4 outputs -Type of input protection- circuit breaker or equivalent -Battery type- Lead-acid battery -Recharge time: 6 hours or more -Nominal Battery Volatge at least 12V -Battery: at least 84 Volt-Amp-Hour Capacity -Control Panel- LED status display with online: on battery -Must have audible alarm when on battery, distinctive alarm when low battery, and continuous tone alarm when owended						
services With bundle uninterrupted power supply Technical Specifications: -At least 360 Watts/650VA -Output Frequency: -50/60 Hz +/- 1 Hz Sync to mains -Topology- Line interactive or any topology that would protect the end user againts the following: power failure, power sag, power surge, under voltage and over-voltage. -Waveform type- within the ranges of stepped approximation sinewave to a pure sinewave -Transfer time: at most 10ms -Input Frequency- 50/60 Hz +/- 3 Hz Autosensing -Input voltage range for main operations: 140V to 300V or higher -Number of Power Cords-1 -Has at least 4 outputs -Type of input protection- circuit breaker or equivalent -Battery type- Lead-acid battery -Recharge time: 6 hours or more -Nominal Battery Volatge at least 12V -Battery: at least 84 Volt-Amp-Hour Capacity -Control Panel- LED status display with online: on battery -Must have audible alarm when on battery, distinctive alarm when low battery, and						
services With bundle uninterrupted power supply Technical Specifications: -At least 360 Watts/650VA -Output Frequency: -50/60 Hz +/- 1 Hz Sync to mains -Topology- Line interactive or any topology that would protect the end user againts the following: power failure, power sag, power surge, under voltage and over-voltage. -Waveform type- within the ranges of stepped approximation sinewave to a pure sinewave -Transfer time: at most 10ms -Input Frequency- 50/60 Hz +/- 3 Hz Autosensing -Input voltage range for main operations: 140V to 300V or higher -Number of Power Cords-1 -Has at least 4 outputs -Type of input protection- circuit breaker or equivalent -Battery type- Lead-acid battery -Recharge time: 6 hours or more -Nominal Battery Volage at least 12V -Battery: at least 84 Volt-Amp-Hour Capacity -Control Panel- LED status display with online: on battery -Must have audible alarm when on battery,						
services With bundle uninterrupted power supply Technical Specifications: -At least 360 Watts/650VA -Output Frequency: -50/60 Hz +/- 1 Hz Sync to mains -Topology- Line interactive or any topology that would protect the end user againts the following: power failure, power sag, power surge, under voltage and over-voltage. -Waveform type- within the ranges of stepped approximation sinewave to a pure sinewave -Transfer time: at most 10ms -Input Frequency- 50/60 Hz +/- 3 Hz Autosensing -Input voltage range for main operations: 140V to 300V or higher -Number of Power Cords-1 -Has at least 4 outputs -Type of input protection- circuit breaker or equivalent -Battery type- Lead-acid battery -Recharge time: 6 hours or more -Nominal Battery Volatge at least 12V -Battery: at least 84 Volt-Amp-Hour Capacity -Control Panel- LED status display with online: on battery						
services With bundle uninterrupted power supply Technical Specifications: -At least 360 Watts/650VA -Output Frequency: -50/60 Hz +/- 1 Hz Sync to mains -Topology- Line interactive or any topology that would protect the end user againts the following: power failure, power sag, power surge, under voltage and over-voltage. -Waveform type- within the ranges of stepped approximation sinewave to a pure sinewave -Transfer time: at most 10ms -Input Frequency- 50/60 Hz +/- 3 Hz Autosensing -Input voltage range for main operations: 140V to 300V or higher -Number of Power Cords-1 -Has at least 4 outputs -Type of input protection- circuit breaker or equivalent -Battery type- Lead-acid battery -Recharge time: 6 hours or more -Nominal Battery Voltage at least 12V -Battery: at least 4 Volt-Amp-Hour Capacity -Control Panel- LED status display with	-					
services With bundle uninterrupted power supply Technical Specifications: -At least 360 Watts/650VA -Output Frequency: -50/60 Hz +/- 1 Hz Sync to mains -Topology- Line interactive or any topology that would protect the end user againts the following: power failure, power sag, power surge, under voltage and over-voltage. -Waveform type- within the ranges of steeped approximation sinewave to a pure sinewave -Transfer time: at most 10ms -Input Frequency- 50/60 Hz +/- 3 Hz Autosensing -Input voltage range for main operations: 140V to 300V or higher -Number of Power Cords-1 -Has at least 4 outputs -Type of input protection- circuit breaker or equivalent -Battery type- Lead-acid battery -Recharge time: 6 hours or more -Nominal Battery Volatge at least 12V -Battery: at least 84 Volt-Amp-Hour Capacity						
services With bundle uninterrupted power supply Technical Specifications: -At least 360 Watts/650VA -Output Frequency: -50/60 Hz +/- 1 Hz Sync to mains -Topology- Line interactive or any topology that would protect the end user againts the following: power failure, power sag, power surge, under voltage and over-voltage. -Waveform type- within the ranges of stepped approximation sinewave to a pure sinewave -Transfer time: at most 10ms -Input Frequency: 50/60 Hz +/- 3 Hz Autosensing -Input Voltage range for main operations: 140V to 300V or higher -Number of Power Cords-1 -Has at least 4 outputs -Type of input protection- circuit breaker or equivalent -Battery type- Lead-acid battery -Bettery type- Lead-acid battery -Bettery type- Lead-acid battery						
services With bundle uninterrupted power supply Technical Specifications: -At least 360 Watts/650VA -Output Frequency: -50/60 Hz +/- 1 Hz Sync to mains -Topology- Line interactive or any topology that would protect the end user againts the following: power failure, power sag, power surge, under voltage and over-voltage. -Waveform type- within the ranges of stepped approximation sinewave to a pure sinewave -Transfer time: at most 10ms -Input Frequency- 50/60 Hz +/- 3 Hz Autosensing -Input voltage range for main operations: 140V to 300V or higher -Number of Power Cords-1 -Has at least 4 outputs -Type of input protection- circuit breaker or equivalent -Battery type- Lead-acid battery	-					
services With bundle uninterrupted power supply Technical Specifications: -At least 360 Watts/650VA -Output Frequency: -50/60 Hz +/- 1 Hz Sync to mains -Topology- Line interactive or any topology that would protect the end user againts the following: power failure, power sag, power surge, under voltage and over-voltage. -Waveform type- within the ranges of stepped approximation sinewave to a pure sinewave -Transfer time: at most 10ms -Input Frequency- 50/60 Hz +/- 3 Hz Autosensing -Input Voltage range for main operations: 140V to 300V or higher -Number of Power Cords-1 -Has at least 4 outputs -Type of input protection- circuit breaker or equivalent						
services With bundle uninterrupted power supply Technical Specifications: -At least 360 Watts/650VA -Output Frequency: -50/60 Hz +/- 1 Hz Sync to mains -Topology- Line interactive or any topology that would protect the end user againts the following: power failure, power sag, power surge, under voltage and over-voltage. -Waveform type- within the ranges of stepped approximation sinewave to a pure sinewave -Transfer time: at most 10ms -Input Frequency- 50/60 Hz +/- 3 Hz Autosensing -Input voltage range for main operations: 140V to 300V or higher -Number of Power Cords-1 -Has at least 4 outputs -Type of input protection- circuit breaker or						
services With bundle uninterrupted power supply Technical Specifications: -At least 360 Watts/650VA -Output Frequency: -50/60 Hz +/- 1 Hz Sync to mains -Topology- Line interactive or any topology that would protect the end user againts the following: power failure, power sag, power surge, under voltage and over-voltage. -Waveform type- within the ranges of stepped approximation sinewave to a pure sinewave -Transfer time: at most 10ms -Input Frequency- 50/60 Hz +/- 3 Hz Autosensing -Input voltage range for main operations: 140V to 300V or higher -Number of Power Cords-1 -Has at least 4 outputs						
services With bundle uninterrupted power supply Technical Specifications: -At least 360 Watts/650VA -Output Frequency: -50/60 Hz +/- 1 Hz Sync to mains -Topology- Line interactive or any topology that would protect the end user againts the following: power failure, power sag, power surge, under voltage and over-voltage. -Waveform type- within the ranges of stepped approximation sinewave to a pure sinewave -Transfer time: at most 10ms -Input Frequency- 50/60 Hz +/- 3 Hz Autosensing -Input voltage range for main operations: 140V to 300V or higher -Number of Power Cords-1						
services With bundle uninterrupted power supply Technical Specifications: -At least 360 Watts/650VA -Output Frequency: -50/60 Hz +/- 1 Hz Sync to mains -Topology- Line interactive or any topology that would protect the end user againts the following: power failure, power sag, power surge, under voltage and over-voltage. -Waveform type- within the ranges of stepped approximation sinewave to a pure sinewave -Transfer time: at most 10ms -Input Frequency- 50/60 Hz +/- 3 Hz Autosensing -Input voltage range for main operations:						
services With bundle uninterrupted power supply Technical Specifications: -At least 360 Watts/650VA -Output Frequency: -50/60 Hz +/- 1 Hz Sync to mains -Topology- Line interactive or any topology that would protect the end user againts the following: power failure, power sag, power surge, under voltage and over-voltage. -Waveform type- within the ranges of stepped approximation sinewave to a pure sinewave -Transfer time: at most 10ms -Input Frequency- 50/60 Hz +/- 3 Hz Autosensing						
services With bundle uninterrupted power supply Technical Specifications: -At least 360 Watts/650VA -Output Frequency: -50/60 Hz +/- 1 Hz Sync to mains -Topology- Line interactive or any topology that would protect the end user againts the following: power failure, power sag, power surge, under voltage and over-voltage. -Waveform type- within the ranges of stepped approximation sinewave to a pure sinewave -Transfer time: at most 10ms -Input Frequency- 50/60 Hz +/- 3 Hz	5					
services With bundle uninterrupted power supply Technical Specifications: -At least 360 Watts/650VA -Output Frequency: -50/60 Hz +/- 1 Hz Sync to mains -Topology- Line interactive or any topology that would protect the end user againts the following: power failure, power sag, power surge, under voltage and over-voltage. -Waveform type- within the ranges of stepped approximation sinewave to a pure sinewave -Transfer time: at most 10ms						
services With bundle uninterrupted power supply Technical Specifications: -At least 360 Watts/650VA -Output Frequency: -50/60 Hz +/- 1 Hz Sync to mains -Topology- Line interactive or any topology that would protect the end user againts the following: power failure, power sag, power surge, under voltage and over-voltage. -Waveform type- within the ranges of stepped approximation sinewave to a pure sinewave						
services With bundle uninterrupted power supply Technical Specifications: -At least 360 Watts/650VA -Output Frequency: -50/60 Hz +/- 1 Hz Sync to mains -Topology- Line interactive or any topology that would protect the end user againts the following: power failure, power sag, power surge, under voltage and over-voltage. -Waveform type- within the ranges of stepped approximation sinewave to a pure						
services With bundle uninterrupted power supply Technical Specifications: -At least 360 Watts/650VA -Output Frequency: -50/60 Hz +/- 1 Hz Sync to mains -Topology- Line interactive or any topology that would protect the end user againts the following: power failure, power sag, power surge, under voltage and over-voltage.						
services With bundle uninterrupted power supply Technical Specifications: -At least 360 Watts/650VA -Output Frequency: -50/60 Hz +/- 1 Hz Sync to mains -Topology- Line interactive or any topology that would protect the end user againts the following: power failure, power sag, power						
services With bundle uninterrupted power supply Technical Specifications: -At least 360 Watts/650VA -Output Frequency: -50/60 Hz +/- 1 Hz Sync to mains -Topology- Line interactive or any topology that would protect the end user againts the						
services With bundle uninterrupted power supply Technical Specifications: -At least 360 Watts/650VA -Output Frequency: -50/60 Hz +/- 1 Hz Sync to mains -Topology- Line interactive or any topology						
services With bundle uninterrupted power supply Technical Specifications: -At least 360 Watts/650VA -Output Frequency: -50/60 Hz +/- 1 Hz Sync to mains						
services With bundle uninterrupted power supply Technical Specifications: -At least 360 Watts/650VA -Output Frequency: -50/60 Hz +/- 1 Hz Sync						
services With bundle uninterrupted power supply Technical Specifications: -At least 360 Watts/650VA						
services With bundle uninterrupted power supply	-At least 360 Watts/650VA					
services						
	With bundle uninterrupted power supply					
	services					
At loast 2 years warranty on parts and						

Caruncho Avenue, Brgy. San Nicolas, Pasig City, Philippines 1600

(02) 8643-1111 * (02) 8641-1111 loc 1461 * bidsandawards@pasigcity.gov.ph *

Page 3 of 6 | RFQ No. 100-24-01-068 | RLD

	Su	ıbTotal:	35,000.00	
Note: Other terms and conditions are stipulated in the atta Terms of Reference, if any.	ched	Total	734,396.16	

DELIVERY TERM: Within Forty-five (45) calendar days upon the receipt of Notice to Proceed.

*Indicate the BRAND NAME or MANUFACTURER NAME and the specific MODEL to be offered or attach a BROCHURE for the offered item; items including but not limited to clothing, vehicle, equipment, devices, electronics, machines, drugs, medicines, medical supplies must be branded or at the very least, manufacturer shall be indicated.

TERMS OF REFERENCE PR 100-24-01-068

PROJECT TITLE: PROCUREMENT OF COMPUTER DESKTOP, LAPTOP AND PRINTER PHILHEALTH EKONSULTA

- 1. PROJECT DESCRIPTION: For the use of City Health Department under PhilHealth EKonsulta
- 2. PROJECT SCOPE OF WORK:

Laptop, computer desktop and printer to provide to various Health centers under Philhealth Ekonsulta electronic Medical record for data encoding of patients.

- 3. SPECIFIC REQUIRMENTS:
 - The Supplier shall guarantee a seven (7) working day period for any minor repairs of the Unit(s) upon
 receipt of the request or report of the recipient unless the cause of the damage is beyond repair due to
 improper use and care without any fault or defect from the manufacturer. The supplier shall also ensure
 the availability of required spare parts of the hardware items to guarantee prompt repairs within the
 specified period.
- 4. The Warranty periods are as follow:
 - The response time to act on the notice for the repair and replacement of defective parts units is within twenty-four (24) hours upon receipt of written or verbal notice from the procuring office. and provide technical assistance to the end user.
 - The supplier shall submit a warranty certificate within seven (7) working days from the date of acceptance by the procuring office.
 - 2 years warranty period on parts and labor
- 5. Delivery : 45 Calendar days from the date of notice to proceed
 - 1. The units shall be delivered to OGS warehouse at Sto.Tomas, Pasig City
- 6. BASIS OF PAYMENT:

Terms: One hundred percent (100%) of the Contract Price upon completion of project from delivery and acceptance of the items.

- 7. OTHER CONDITIONS AND CHANCE OF SPECIFICATIONS:
 - The unit laptop, desktop and printer must be a reputable brand.
 - The units of laptop, computer desk top and printer must be in the Philippine market for at least 5 years.

Caruncho Avenue, Brgy. San Nicolas, Pasig City, Philippines 1600

(02) 8643-1111 * (02) 8641-1111 loc 1461 * 🖄 bidsandawards@pasigcity.gov.ph *

Page 4 of 6 | RFQ No. 100-24-01-068 | RLD

Submit this Quotation (Accomplished and duly signed by the Owner or the respective Authorized Representative indicated in the Secretary's Certificate/Special Power of Attorney) not later than the closing date specified in the Bid Notice Abstract posted in PhilGEPS website along with the following documents:

- Mayor's/Business Permit (or a recently expired Mayor's/Business permit together with the official receipt as proof that the prospective bidder has applied for renewal within the period prescribed by the concerned local government unit subject to submission of the Mayor's Permit before the award of contract). The nature of business as stated in the Mayor's/Business Permit should at the very least be similar or related to the project to be bid.
- PhilGEPS Registration Number
- **Income Tax Return** Latest Income or Business Tax Returns filed and paid through the BIR Electronic Filing and Payment System (EFPS).

In accordance with Revenue Regulation No. 3-2005, the above-mentioned tax returns shall refer to the following:

- 1. Latest Income Tax Return (ITR) For participants already with an Annual ITR, latest ITR shall refer to the ITR for the preceding Tax Year be it on a calendar or fiscal year. For new establishments which, therefore, have no annual ITR yet, it shall refer to the most recent guarter's ITR.
- 2. Latest Business Tax Return refers to the Value Added Tax (VAT) or Percentage Tax returns covering the previous six (6) months.
- Accomplished and notarized Omnibus Sworn Statement (Form can be downloaded thru <u>https://www.gppb.gov.ph/downloadable-forms/#tab-61412</u>)
- **Proof of Authorization: Secretary's Certificate** if corporation, or **Special Power of Attorney**, if individual.

ADDITIONAL REQUIREMENTS:

For Procurement of Drugs and Medicines:

Documents from the Food and Drug Administration (FDA):

- a. Certificate of Product Registration;
- b. Certificate of Good Manufacturing Practice;
- c. License to Operate;
- d. Batch Release Certificate (for vaccines, toxoids and immunoglobulins only) [to be submitted upon delivery]; and
- e. Certificate of Analysis (for anesthesia and antibiotics) [to be submitted upon delivery].

If the Supplier is not the Manufacturer, a certification from the Manufacturer that the supplier is an authorized distributor/dealer of the products/items.

Please submit the accomplished Quotation and required documents on or before the deadline of submission at the Bids and Awards Committee (BAC) through the **Procurement Management Office (BAC Secretariat Office)**, <u>4th Floor</u>, **Pasig City Hall, San Nicolas, Pasig City**.

All documents should be submitted in a sealed brown envelope addressed to the "Bids and Awards Committee, 4th Floor, Pasig City Hall", and properly marked with the Project Title as provided herein.

The CITY GOVERNMENT OF PASIG reserves the right to reject any and all bids, declare a failure of bidding, or not award the contract at any time prior to contract award in accordance with Sections 35.6 and 41 of the 2016 revised IRR of RA No. 9184, without thereby incurring any liability to the affected bidder or bidders.

Caruncho Avenue, Brgy. San Nicolas, Pasig City, Philippines 1600

(02) 8643-1111 * (02) 8641-1111 loc 1461 * main pasigcity.gov.ph * main pasigcity.gov.ph For any clarification, you may contact us at telephone no. (02) 8641-1111 / (02) 8643-1111 loc. 1461 or email address at <u>bidsandawards@pasigcity.gov.ph</u>

SGD

ATTY. BEA THERESE P. VILLANUEVA Officer in Charge, Procurement Management Office

I hereby certify that I have read and agree to this Request for Quotation, its Terms of Reference, and Bid Bulletin/s, if any. I further certify that the products to be delivered will conform to the specifications stated in the Item Description.

Conforme:

Signature over Printed Name

Position

Duly authorized to sign quotation/offer for and on behalf of ____

(Please indicate Company Name)

Caruncho Avenue, Brgy. San Nicolas, Pasig City, Philippines 1600